## IN THE CLAIMS

(currently amended) An information processing apparatus, comprising:

a generator operable to generate a Bridge Clip AV clip information that includes address stream information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream,

said Bridge Clip AV stream consisting of a preset portion of a first AV stream and a preset portion of a second AV stream without changes to the preset portion of the first AV stream and without changes to the preset portion of the second AV stream, and being reproduced when reproduction is switched from said first AV stream to said second AV stream,

said address information including:

information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, and

information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream; and

a recorder operable to record said Bridge Clip AV said clip information generated by said stream generator;

wherein said Bridge Clip ΑV stream continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream,

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

- (previously presented) The information processing apparatus according to claim 1, wherein an arrival time stamp of said source packet of said first AV stream is continuous with an arrival time stamp of a first source packet located at a leading end of said third AV stream, and an arrival time stamp of said source packet of said second AV stream is continuous with an arrival time stamp of a second source packet located at a trailing end of said third AV stream.
- information (previously presented) The processing apparatus according to claim 2, wherein a sole discontinuous point exists in said arrival time stamp of said second source packet in said third AV stream.
- (original) The information processing apparatus according to claim 2, wherein said address is determined so that a data portion of an AV stream previous to a source packet specified by said information on said address of said source packet of said first AV stream is located in a continuous area of not less than a preset size on a recording medium.
- (original) The information processing apparatus according to claim 2, wherein said address is determined so that a data portion of an AV stream subsequent to a source packet specified by said information on said address of said source packet of said second AV stream is located in a continuous area of not less than a preset size on a recording medium.
- information processing apparatus 6. (original) The according to claim 2, wherein said third AV stream is generated so that said third AV stream is located in a continuous area of not less than a preset size on said recording medium.

7. (currently amended) An information generating method, comprising:

generating a Bridge Clip AV stream consisting of a preset portion of a first AV stream and a preset portion of a second AV stream without changing the preset portion of the first AV stream and without changing the preset portion of the second AV stream, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream; and

generating clip information that includes address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream,

said address information including:

information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, and

information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream;

wherein said Bridge Clip AV stream maintains continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream.

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

8. (currently amended) A recording medium having recorded thereon a computer-readable program for carrying out a method of generating information, said method comprising:

generating a Bridge Clip AV stream consisting of a preset portion of a first AV stream and a preset portion of a second AV stream without changing the preset portion of the first AV stream and without changing the preset portion of the second AV stream, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream; and

generating clip information that includes address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream,

said address information including:

information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, and

information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream;

wherein said Bridge Clip AV stream maintains continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream.

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

9. (cancelled)

10. (currently amended) An information processing apparatus, comprising:

a reproducing unit operable to reproduce a recording medium having recorded thereon a first AV stream, a second AV stream, a Bridge Clip AV stream consisting of a preset portion of said first AV stream and a preset portion of said second AV stream without changes to the preset portion of the first AV stream and without changes to the preset portion of the second AV stream, and clip information that includes address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream, said address information including information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, and information on an address of a source packet of at a time of switching said second ΑV stream reproduction from said third AV stream to said second AV stream; and

a controller operable to control said reproducing unit for switching reproduction from said first AV stream read out from said first AV stream to said Bridge Clip AV stream and from said Bridge Clip AV stream to said second AV stream, based on said information pertinent to said Bridge Clip AV stream, read out from said second AV stream;

maintains wherein said Bridge Clip ΑV stream continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream,

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

(currently amended) An information processing method, comprising:

reproducing a recording medium having recorded thereon a first AV stream, a second AV stream, a Bridge Clip AV stream consisting of a preset portion of said first AV stream and a preset portion of said second AV stream without changes to the preset portion of the first AV stream and without changes to the preset portion of the and clip information that stream, second AV address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream, said address information including information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream; and

controlling said reproducing for step reproduction from said first AV stream readout-controlled in a first readout controlling step to said Bridge Clip AV stream and from said Bridge Clip AV stream to said second AV stream, based on said information pertinent to said Bridge Clip AV stream, readout-controlled in a second readout controlling step;

stream maintains said Bridge Clip AV wherein continuity to achieve a seamless playback and said clip

stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream,

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

(currently amended) A recording medium having recorded 12. thereon a computer-readable program for carrying out a method of processing information, said method comprising:

reproducing a recording medium having recorded thereon a first AV stream, a second AV stream, a Bridge Clip AV stream consisting of a preset portion of said first AV stream and a preset portion of said second AV without changes to the preset portion of the first stream and without changes to the preset portion of the information that includes and clip ΑV stream, second address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream, said address information including information on an address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream; and

reproducing step for switching said controlling reproduction from said first AV stream readout-controlled in a first readout controlling step to said Bridge Clip AV stream and from said Bridge Clip AV stream to said second AV stream, based on said information pertinent to said

readout-controlled in a second Bridge Clip AV stream, readout controlling step;

said Bridge Clip AV stream maintains wherein continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream,

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.

- 13. (cancelled)
- 14. (currently amended) A computer-readable recording medium having recorded thereon address information, the address information comprising:

a Bridge Clip AV stream consisting of a preset portion of said first AV stream and a preset portion of said second AV stream without changes to the preset portion of the first AV stream and without changes to the preset portion of the second AV stream,, said Bridge Clip AV stream being reproduced when reproduction is switched from said first AV stream to said second AV stream; and

clip information that includes address information as information pertinent to said Bridge Clip AV stream and clip stream type information for the Bridge Clip AV stream, information including information on said address address of a source packet of said first AV stream at a time of switching of reproduction from said first AV stream to a third AV stream, and information on an address of a source packet of said second AV stream at a time of switching of reproduction from said third AV stream to said second AV stream;

wherein said Bridge Clip AV stream maintains continuity to achieve a seamless playback and said clip stream type information included in the clip information for said Bridge Clip AV stream indicates that said third AV stream is a Bridge Clip AV stream,

said Bridge Clip AV stream including enough data to enable continuous playback from a record medium during a time when a playback head jumps from one location on the record medium to another location on the record medium.